

ZHEJIANG FLAMETECH INDUSTRIES CO.,LTD

5KG CO2 Fire Extinguisher, EN3 certificate



Product Name	CO2 Fire Extinguisher	
Product Code	FT02-03D-00	
Out-diameter(mm)	∲ 135.8	
Cylinder high (mm)	650	
Cylinder weight (kg)	7.9	
Extinguisher weight(kg)	13.5	
Volume (L)	7.5	
Filling Charge	5kg CO2	
Temperature range (°C)	-30° C~+60° C	
Working Pressure (bar)	174	
Test pressure (bar)	250	
Material	34Cr m04	
Fire rating	89B	
Packing Specification (mm)	170*145*770	

ADD: Tianjia Village, Xiaoyue Town, Shangyu City, Zhejiang, China.

TEL:+86-575-82719238 FAX:+86-575-82718175

E-mail:info@flametech-co.com Website: www.flametech-co.com

ZIP:312367





Product Name	Dry Powder Fire Extinguisher
Product Code	FT01-06A-00
Out-diameter(mm)	Φ160
Cylinder high (mm)	427
Cylinder weight (kg)	2.82
Extinguisher weight(kg)	9.45
Volume (L)	7.6
Filling Charge	6kg 40%ABC (EN615)
Temperature range (°C)	-20° C~+60° C
Working Pressure (bar)	15
Test pressure (bar)	30
Material	DC01
Fire rating	34A 183B
Packing Specification (mm)	170*170*535

ADD: Tianjia Village, Xiaoyue Town, Shangyu City, Zhejiang, China.

TEL:+86-575-82719238 FAX:+86-575-82718175

E-mail:info@flametech-co.com Website: www.flametech-co.com

ZIP:312367



Zhejiang FlameTech ▲M≡ Industries Co. Ltd

Product: Foam fire extinguisher Model No.: FT01-06A-00/CE1 Approval: BSI/Kitemark - KM 569890



Product Name Foam Fire Extinguisher Product Code FT01-06A-00/CE1 Out-diameter(mm) Φ160 Cylinder high (mm) 433 Cylinder weight (kg) 2.8 Extinguisher weight(kg) 9.5 Volume (L) 7.2 **Filling Charge** 6LAFFF3% Temperature range (° C) +5° C~+60° C Working Pressure (bar) 15 30 Test pressure (bar) Material DC01 13A 144B Fire rating 170*170*575 Packing Specification (mm)

ADD: Tianjia Village, Xiaoyue Town, Shangyu City, Zhejiang, China.

TEL:+86-575-82719238 FAX:+86-575-82718175

E-mail:info@flametech-co.com Website: www.flametech-co.com

ZIP:312367

Fire Blanket Specification

Product Description

Product	Fiberglass Fire blanket
Model	CWT380
Material	100% fiberglass fabric, fiberglass thread, fire resistant tabs
Regular Size	1.0m*1.0m 1.2m*1.2m 1.2*1.5m 1.2m*1.8m 1.8m*1.8m Different size can be customized.
Certificate	TUV/ EN1869:1997/ REACH/ ASTM F 1989/ PAHS
High temperature resistant	Above 550°C
Thickness	0.43mm
Weight	430g/m2
Package	Soft PVC bag or Rigid red PVC box
Product introduction	Fire blanket is a specially treated glass fiber fabric which is very soft, smooth and does not irritate skin. Which use fiberglass thread to sew the fold and fire resistance ribbon. So the crafts ensure the whole fire resistance, Our products have passed standard of European EN-1869:1997 & REACH and American ASTM F 1989. Since Fire Blanket is a kind of very soft fire distinguishing device. At the very beginning of a fire accident, it can be used to insulate the fire from oxygen, thus controlling the fire. The thickness of the fire blanket is 0.43mm. In an emergency, it is a perfective covering, isolating our body from the heat source during an escape. it can be easily wrapped on any irregular objects. When compared with the other kinds of fire distinguishers, fire blanket has the following advantages:
	 A. It has no expiry date. B. It is environmental friendly. C. It is a good insulator and high temperature resistance. Fire blanket is easy to carry & store and simple to use. It is the best choice for emergency, fire protection and fire fighting. Ideal for use in kitchen, hotel, garage, gas station, laboratory, BBQ etc.

